

jdrutils

Version 1.4

Nicola Talbot

29th April, 2012

Abstract

Jpgfdraw comes with a number of command line applications for converting JDR and AJR files to other formats. This document describes those applications.

Contents

1	ajr2jdr	1
2	jdr2ajr	2
3	jdr2eps	2
4	jdr2png	3
5	jdr2svg	3
6	jdr2tex	3
7	eps2jdr	4

1 ajr2jdr

Syntax:

```
ajr2jdr [<options>] <ajr file> <jdr file>
```

Purpose:

Converts an AJR file (specified by *<ajr file>*) to a JDR file (specified by *<jdr file>*.)

Options:

- settings** [*<n>*] Controls how settings are saved in the output file. Optionally followed by an integer *<n>* (if omitted *<n>*=1):
 - 0** don't save settings
 - 1** save all settings
 - 2** only save paper size (v1.3 only, for earlier versions equivalent to 0)
- nosettings** Equivalent to **-settings 0**

- settings_as_input** Only save settings if they were given in the input file (Default)
- v1.0** Use version 1.0 for the output format. (You may lose information if the input file has a higher version number.)
- v1.1** Use version 1.1 for the output format. (You may lose information if the input file has a higher version number.)
- v1.2** Use version 1.2 for the output format.
- v1.3** Use version 1.3 for the output format.
- v1.4** Use version 1.4 for the output format. (Default)

2 jdr2ajr

Syntax:

```
jdr2ajr [<options>] <jdr file> <ajr file>
```

Purpose:

Converts a JDR file (specified by *<jdr file>*) to an AJR file (specified by *<ajr file>*.)

Options:

- settings** [*<n>*] Controls how settings are saved in the output file. Optionally followed by an integer *<n>* (if omitted *<n>*=1):
 - 0** don't save settings
 - 1** save all settings
 - 2** only save paper size (v1.3 only, for earlier versions equivalent to 0)
- nosettings** Equivalent to **-settings 0**
- settings_as_input** Only save settings if they were given in the input file (Default)
- v1.0** Use version 1.0 for the output format. (You may lose information if the input file has a higher version number.)
- v1.1** Use version 1.1 for the output format. (You may lose information if the input file has a higher version number.)
- v1.2** Use version 1.2 for the output format.
- v1.3** Use version 1.3 for the output format.
- v1.4** Use version 1.4 for the output format. (Default)

3 jdr2eps

Syntax:

```
jdr2eps <jdr file> <eps file>
```

Purpose:

Converts a JDR file to an EPS file.

Limitations:

Transparency is not implemented.

4 **jdr2png**

Syntax:

```
jdr2png <jdr file> <png file>
```

Purpose:

Converts a JDR file to a PNG file.

Limitations:

The output file will use always RGB colour space. Any CMYK specifications will be converted to RGB. The background colour will be white not transparent.

5 **jdr2svg**

Syntax:

```
jdr2svg <jdr file> <svg file>
```

Purpose:

Converts a JDR file to an SVG file.

Limitations:

Gradient paint is not available for line or text colour.

6 **jdr2tex**

Syntax:

```
jdr2tex <jdr file> <tex file>
```

Purpose:

Converts a JDR file to a \LaTeX file containing a `pgfpicture` environment.

Limitations:

Gradient paint is not available for line or text colour.

7 eps2jdr

Syntax:

```
eps2jdr [options] <eps file> <jdr file>
```

Options:

- bitmap** <basename> Extract bitmaps to be saved as <basename><n>.png.
- v1.0** Save as JDR version 1.0
- v1.1** Save as JDR version 1.1
- v1.2** Save as JDR version 1.2
- v1.3** Save as JDR version 1.3
- v1.4** Save as JDR version 1.4 (default)
- normalsize** <n> Set the normal LaTeX font size to <n>
- verbose** Verbose output
- version** Print current version number and exit

Purpose:

Converts an Encapsulated PostScript file to a JDR file.

Limitations:

Jpgfdraw doesn't have anything like the functionality of PostScript, so there are many limitations. There are many PostScript commands that are either not implemented at all or only work in a limited way. If **eps2jdr** doesn't work on an EPS file, try using **eps2eps** on the EPS file and try on the output of that. However there is still no guarantee that it will work.

If **eps2jdr** can't implement a PostScript command, it will do one of the following:

1. Find the nearest approximation
2. Print a warning message and ignore the command (popping any operands off the stack where necessary)
3. Print an error message, and exit.

If the EPS file contains images (via the **image** or **colorimage** operators), each image will be extracted and saved as a PNG file with name <basename><n>.png, where <basename> is the basename of the output JDR file, unless the **-bitmap** option was used.

Font substitutions may occur, but you can create a PostScript to L^AT_EX font map in Jpgfdraw's configuration directory¹. To do this, use your favourite text editor to create a file called **psfontmap**. Each line must be in the form:

```
<PostScript font name>=<Family declaration>,<Series declaration>,<Shape declaration>
```

The PostScript font name may be a regular express. For example:

```
.*obliquebold=,\bfseries,\slshape
```